



DECO PRODUCTS, INC.

DECO TravaCast

High Shine Sealer

Single Component, High Gloss Shine

Product specification

DECO TravaCast is a single component, film forming, non hazardous coating designed to enhance and seal concrete pavers, natural stones, travertine and other similar surfaces. DECO TravaCast adds excellent stain resistance from most common drips and spills. Deco TravaCast can be used to enhance, seal and protect your new project or restore and revive your existing project.

Non- Hazardous

Environmentally Friendly

B E N E F I T S

- Extra protection against most stains
- Provides surface protection from possible damage
- Looks more vibrant
- Excellent adhesion
- Helps reduce the chance of discoloration
- Beautiful shine
- Dries quick
- Outlasts most other industrial coatings
- Non- hazardous Non- toxic Non- flammable



Made in the U.S.A.



Use: For approved applicators

New & existing construction: TravaCast is a water tight barrier that will enhance your substrates appearance. TravaCast is an excellent product for enhancing old worn out materials or protecting your new install. TravaCast is a single component sealer that does not require any additives or other activators saving you time and money with installation. Only one coat is required. The use of an anti-slip material should be used for best results and safety.

SPECIFICATION DATA

PRODUCT BENEFITS

Chemical/Stain Resistance
Excellent Adhesion
Water Blushing Resistant
UV Protected
Enhances Surfaces

LIMITATIONS

Do not let product freeze. Do not dilute with water. Store indoors at temperatures above 32 degrees Fahrenheit. Do not apply product when temperatures are below 50 degrees Fahrenheit and above 80 degrees Fahrenheit. Use caution when applying on windy days and do not install when rain is imminent. Deco TravaCast is not intended to be used as a slip resistant coating. **The use of an anti-slip material should be used for best results and safety.**

PREPARATION:

Use Deco's Super StripaCast if the surface has been previously sealed. Clean substrate thoroughly with power washer removing all loose dirt, oils and foreign objects. Repair all cracked or damaged grout lines and deficiencies. Allow substrate plenty of time to dry to prevent trapping moisture behind the coating and harming the products effectiveness.

STORAGE: TravaCast's average shelf life is eight months from the date of manufacturing when stored in climate controlled conditions between 35 and 85 degrees and out of direct sunlight. TravaCast is sensitive to multivalent ions such as: iron, copper, zinc and aluminum. Stability of TravaCast can be compromised if contact occurs. This applies to storage tanks, pipes, mixers or containers.

As a leading manufacturer of sealers and coatings, Deco Products, Inc. is committed to providing customers with environmentally friendly products that meet the highest standards of quality available today.

PRODUCT SPECIFICATIONS

Solids Content- 49.0
pH- 7.5 +/-
Appearance- Clear/ transparent
Viscosity- 89-92 KU
Solvent Content- 0%

APPLICATION:

Apply DECO TravaCast without dilution to Travertine or other qualified materials with a low pressure pneumatic canister or garden type hand pump sprayer. Do not flood coat. Use a fine mist and apply to substrate until wet, avoiding puddling, drips and runs. Use a micro fiber mop or paint roller to even out any puddles or over applications. Allow a recommended minimum dry time of 24 hours before walking on and 72 hours before replacing furniture. Do not place rugs or carpets for at least 3 weeks. Times vary due to factors beyond our control.

WARRANTY:

DECO Products, Inc. warrants its products to be of the highest quality and will replace or refund the purchase price of the product if proven defective within 3 months of date of purchase. It is the buyers responsibility to determine that the product meets their needs and should be applied by a skilled applicator. Always perform a jobsite test prior to complete application to ensure desired results.

IMPORTANT: The descriptions, designs and data contained herein are presented for guidance only. Because there are many factors out of our control and knowledge which may affect the application, it is necessary that the applicator be skilled in determining potential problems and defects that might prevent our product from reaching desired results.

TECHNICAL SERVICES:

Applicators guides are available on our website or by contacting your local rep. Always read and understand Technical Data, Applicators Guides and SDS before using. Technical advise furnished by Deco Products, Inc concerning any use or application of its products are as reliable as current technology allows. **A slip resistant additive is recommended to avoid slips and falls.**

KEEP OUT OF REACH OF CHILDREN

Recommended equipment:



Distributed by:

J.Racenstein www.jracenstein.com